



- NOTES :
- 1.0. RATING :
  - 1.1. VOLTAGE : 12 VAC (R.M.S.)
  - 1.2. CURRENT : 1 AMPERE MAXIMUM PER CONTACT AT 30°C T-RISE
  - 1.3. TEMPERATURE : -20°C TO +70°C
  - 2.0. ELECTRICAL CHARACTERISTIC :
  - 2.1. CONTACT RESISTANCE : 50 MILLIOHMS MAXIMUM INITIAL
  - 2.2. INSULATION RESISTANCE : 100 MEGOHMS MINIMUM
  - 2.3. DIELECTRIC WITHSTANDING VOLTAGE : 500 VAC AT SEA LEVEL
  - 3.0. MATERIALS :
  - 3.1. CONTACT : COPPER ALLOY
  - 3.2. HOUSING : THERMOPLASTIC, GLASS FILLED, 130°C, UL 94V-0 RATED
  - 4.0. MECHANICAL :
  - 4.1. INSERTION FORCE(PER CONTACT): 300~3000 GRAMS
  - 4.2. WITHDRAWAL FORCE(PER CONTACT): 300~3000 GRAMS
  - 4.3. DURABILITY ,MINIMUM: MATED 5000 TIMES WITHOUT DEGRADING ELECTRICAL CHARACTERISTICS
  - 4.4. CONTACT FORCE, MINIMUM: 80 GRAMS

MEASURE POINT: (QP)  
 QUADRANT POINT (TP)  
 TANGENCY POINT (TD)  
 INTERSECTION POINT (PB)  
 UNLESS OTHERWISE SPECIFIED, TOLERANCE:

±0.25	±0.10	±.3
X	X,XX	ANGULAR



深圳市明达辉电子有限公司  
 SHEN ZHEN MINGDAHUI ELECTRONIC CO., LTD.

DESIGN	DATE	TITLE:
CHECKED	DATE	3. 5孔耳机插座
APPROVED	DATE	
PART NO.: MJKD-0636118-16	REV.: 1	SCALE: 1:1
DRAWING NO.: N/A	SIZE: A4	SHEET: 1/1
		UNIT: mm

REV.	ECN.	NO.	APPD.
1			