

# TEST REPORT

Report No.: BCTC2410830549-1E

---

Applicant: Radxa Computer (Shenzhen) Co.,Ltd.

---

Product Name: Radxa ZERO 3W

---

Test Model: Radxa ZERO 3W D1E0H1W15

---

Tested Date: 2024-10-10 to 2024-11-15

---

Issued Date: 2024-11-15

---

**Shenzhen BCTC Testing Co., Ltd.**



Product Name: Radxa ZERO 3W

Trademark:   
Radxa ZERO 3W D1E0H1W15  
Radxa ZERO 3W D1E0H0W15, Radxa ZERO 3W D2E0H0W15,  
Radxa ZERO 3W D4E0H0W15, Radxa ZERO 3W D8E0H0W15,  
Radxa ZERO 3W D2E0H1W15, Radxa ZERO 3W D4E0H1W15,  
Radxa ZERO 3W D8E0H1W15, Radxa ZERO 3W D1E8H0W15,  
Radxa ZERO 3W D2E16H0W15, Radxa ZERO 3W D4E32H0W15,  
Radxa ZERO 3W D8E64H0W15, Radxa ZERO 3W D1E8H1W15,  
Radxa ZERO 3W D2E16H1W15, Radxa ZERO 3W D4E32H1W15,  
Radxa ZERO 3W D8E64H1W15

Model/Type reference:

Prepared For: Radxa Computer (Shenzhen) Co.,Ltd.

Address: 1602, Smart Valley, tiezai Road, Gongle community, Xixiang, Baoan, Shenzhen, China

Manufacturer: Radxa Computer (Shenzhen) Co.,Ltd.

Address: 1602, Smart Valley, tiezai Road, Gongle community, Xixiang, Baoan, Shenzhen, China

Prepared By: Shenzhen BCTC Testing Co., Ltd.

Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Sample Received Date: 2024-10-10

Sample tested Date: 2024-10-10 to 2024-11-15

Issue Date: 2024-11-15

Report No.: BCTC2410830549-1E

Test Standards: Article 2 paragraph 1 of item 19  
MIC Notice No.88 Appendix No.43

Test Results: PASS

Remark: This is JAPAN RADIO test report.

Tested by:



Lei Chen/Project Handler

Approved by:



Zero Zhou/Reviewer

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.


## Table Of Content

	Page
Test Report Declaration	
1. Version .....	5
2. Test Summary .....	6
3. Measurement Uncertainty .....	7
4. Product Information And Test Setup .....	8
4.1 Product Information.....	8
4.2 Block Diagram Parameters Of Text Software Setting .....	8
4.3 Description Of Support Units (Conducted Mode) .....	8
4.4 Channel List.....	9
4.5 Test Mode .....	10
4.6 Test Conditions .....	10
4.7 Table Of Parameters Of Test Software Setting .....	10
5. Test Facility And Test Instrument Used.....	11
5.1 Test Facility.....	11
5.2 Test Instrument Used.....	11
6. RF Shielding Method.....	12
7. Frequency Error .....	13
7.1 Block Diagram Of Test Setup.....	13
7.2 Limit .....	13
7.3 Measuring Instruments And Setting .....	13
7.4 Test Procedure .....	13
7.5 Test Result.....	14
8. Antenna Power.....	16
8.1 Block Diagram Of Test Setup.....	16
8.2 Limit .....	16
8.3 Measuring Instruments And Setting .....	16
8.4 Test Procedure .....	16
8.5 Test Result.....	17
9. Occupied Bandwidth .....	18
9.1 Block Diagram Of Test Setup.....	18
9.2 Limit .....	18
9.3 Test Procedure .....	18
9.4 Test Result.....	18
10. Unwanted Emission Intensity Measurement.....	22
10.1 Block Diagram Of Test Setup.....	22
10.2 Limit .....	22
10.3 Measuring Instruments And Setting .....	22
10.4 Test Procedure .....	22
10.5 Test Result.....	23
11. Radio Interference Prevention Capability Measurement .....	51
11.1 Block Diagram Of Test Setup.....	51
11.2 Limit .....	51
11.3 Measuring Instruments And Setting .....	51
11.4 Test Procedure .....	51

11.5	Test Result.....	51
12.	Dwell Time.....	52
12.1	Block Diagram Of Test Setup.....	52
12.2	Limit .....	52
12.3	Measuring Instruments And Setting .....	52
12.4	Test Procedure .....	52
12.5	Test Result.....	53
13.	Carrier Sense .....	68
14.	Imitation Of Collateral Emission Of Receiver Measurement.....	69
14.1	Block Diagram Of Test Setup.....	69
14.2	Limit .....	69
14.3	Measuring Instruments And Setting .....	69
14.4	Test Procedure .....	69
14.5	Test Result.....	70
15.	EUT Photographs.....	74
16.	EUT Test Setup Photographs.....	75


(Note: N/A Means Not Applicable)

TEC  
TC  
OVB  
t Sea



**1. Version**

Report No.	Issue Date	Description	Approved
BCTC2410830549-1E	2024-11-15	Original	Valid



## 2. Test Summary

Test procedures according to the technical standards:

<b>Article 2 paragraph 1 of item 19</b>			
Standard Section	Test Item	Judgment	Remark
<b>General provisions</b>			
5	Frequency Error	PASS	
6	Occupied Bandwidth	PASS	
7	Spurious Emissions Intensity	PASS	
8	Radio Interference Prevention Capability Measurement	PASS	
<b>Transmitting equipment</b>			
6	Antenna Power	PASS	
<b>Transmitting antenna</b>			
20	Type, Configuration, etc., of Transmitting Antenna	PASS	
22	Direction Pattern of Transmitting Antenna (Provided at Individual Antenna Report)	PASS	
<b>Receiving antenna</b>			
24	Limitation of Collateral Emission of Receiver	PASS	
26	Refer to All Articles for Transmitting Antenna	PASS	
<b>Operating frequency 2400~2483.5MHz</b>			
49.20(1);a	RF Shielding Method	PASS	
49.20(1);a	Communication Method	PASS	
49.20(1);b	Spread-spectrum Method	PASS	
49.20(1);c	Antenna Power	PASS	
49.20(1);d	Absolute Antenna Gain (Provided at Individual Antenna Report)	PASS	
49.20(1);e	Spread-Spectrum Bandwidth	PASS	
49.20(1);f	Spreading Factor	PASS	
49.20(1);g	Hopping Frequency Dwell Time (FH employed)	PASS	


**NOTE:**

(1) "N/A" denotes test is not applicable in this Test Report.

### 3. Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 3.2\text{dB}$
2	Radiated Emission Test	$\pm 4.7\text{dB}$
3	RF power,conducted	$\pm 0.16\text{dB}$
4	Spurious emissions,conducted	$\pm 0.21\text{dB}$
5	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
6	All emissions,radiated(>1G)	$\pm 5.0\text{dB}$
7	frequency error ppm	$\pm 0.5\text{ppm}$




## 4. Product Information And Test Setup


### 4.1 Product Information

Model/Type reference:	Radxa ZERO 3W D1E0H1W15 Radxa ZERO 3W D1E0H0W15, Radxa ZERO 3W D2E0H0W15, Radxa ZERO 3W D4E0H0W15, Radxa ZERO 3W D8E0H0W15, Radxa ZERO 3W D2E0H1W15, Radxa ZERO 3W D4E0H1W15, Radxa ZERO 3W D8E0H1W15, Radxa ZERO 3W D1E8H0W15, Radxa ZERO 3W D2E16H0W15, Radxa ZERO 3W D4E32H0W15, Radxa ZERO 3W D8E64H0W15, Radxa ZERO 3W D1E8H1W15, Radxa ZERO 3W D2E16H1W15, Radxa ZERO 3W D4E32H1W15, Radxa ZERO 3W D8E64H1W15
Model differences:	All the model are the same circuit and RF module, except model names and appearance of the color.
Hardware Version:	V1.11
Software Version:	b6
Operation Frequency:	2402-2480MHz
Type of Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Number Of Channel:	79 CH
Antenna installation:	Chip antenna 1.5 dBi
Antenna Gain:	Remark: <input checked="" type="checkbox"/> The antenna gain of the product comes from the antenna report provided by the customer, and the test data is affected by the customer information. <input type="checkbox"/> The antenna gain of the product is provided by the customer, and the test data is affected by the customer information.
Ratings:	DC 5V

### 4.2 Block Diagram Parameters Of Text Software Setting



### 4.3 Description Of Support Units (Conducted Mode)

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Radxa ZERO 3W		Radxa ZERO 3W D1E0H1W15	N/A	EUT

#### Notes:

1. The support equipment was authorized by Declaration of Confirmation.
2. For detachable type I/O cable should be specified the length in cm in 『Length』 column
3. “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.



## 4.4 Channel List

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

BCTC  
 BCTC  
 PPR  
 Report

#### 4.5 Test Mode

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanned based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

For All Mode	Description	Modulation Type
Mode 1	CH 00	GFSK
Mode 2	CH 39	
Mode 3	CH 78	
Mode 4	RX	
Mode 5	CH 00	π/4-DQPSK
Mode 6	CH 39	
Mode 7	CH 78	
Mode 8	RX	
Mode 9	CH 00	8DPSK
Mode 10	CH 39	
Mode 11	CH 78	
Mode 12	RX	

#### 4.6 Test Conditions

The EUT was tested while in a continuous transmitter/receiver mode. The EUT was tuned to a low, middle, and high channel for all tests. For all test case pre-scans were completed in all Modes to determine worst case levels.

##### Power Supply Voltage Fluctuation Test

Voltage Fluctuation Test	Normal Voltage	High Voltage +10% of Normal Voltage	Low Voltage -10% of Normal Voltage
Input DC Power	5V	5.5V	4.5V
Voltage Variation (%)	0%	+10%	-10%

Note:

Voltage Variation (%)

= (Output high or Low Voltage - Output Normal Voltage) / Output Normal Voltage \* 100

During the input supply voltage to the EUT from the external power source is varied by ±10%, ±10% of the external power change, will not affect the voltage of the RF, so only operated in normal voltage to test all regulations.

#### 4.7 Table Of Parameters Of Test Software Setting

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters

Test software Version	CMD		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters	DEF	DEF	DEF

## 5. Test Facility And Test Instrument Used

### 5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850

A2LA certificate registration number is: CN1212


ISED Registered No.: 23583

ISED CAB identifier: CN0017

### 5.2 Test Instrument Used

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1.	Power Metter	Keysight	E4419	\	May 16, 2024	May 15, 2025
2.	Signal Analyzer 20kHz-26.5GHz	Keysight	N9020A	MY49100060	May 16, 2024	May 15, 2025
3.	Signal Generator	Keysight	N5182B	MY56200519	May 16, 2024	May 15, 2025
4	Pulse limiter	Schwarzbeck	VTSD 9561-F	01323	May 16, 2024	May 15, 2025
5	Hygrothermograph	Thermo	HTC-1	\	Nov. 13, 2023	Nov. 12, 2024

Calibration laboratory: CCIC(Shenzhen) Co., Ltd



## 6. RF Shielding Method

Chipset:

The product structure is uses SMD patch process.


As shown in the picture, If the will be open so the product be damage.

Number of the pins: 48 interval distance 0.5mm



## 7. Frequency Error

### 7.1 Block Diagram Of Test Setup



### 7.2 Limit

Item	Limits
Frequency Error	±50ppm

### 7.3 Measuring Instruments And Setting

The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
RB / VB	10KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


### 7.4 Test Procedure



- (1) In the case of unmodulated signal (continuous or continuous burst), measure the frequency directly by a frequency meter.
  - (2) In the case of burst waves, the measurement shall be done for enough time in order to obtain the enough measuring accuracy, and the average of the measured values becomes the final value.
  - (3) In the case of a test mode with a specific frequency spectrum, measure the frequency of the specific spectrum by a spectrum analyzer.
  - (4) In the cases above, if the frequency equivalent to the test frequency is not directly measured in principle, it shall be obtained by necessary calculation.
- In the case of modulated signal, if there is no specific spectrum measurable by a spectrum analyzer but a specific dip is observed, it is allowed to measure the frequency with the signal generator (synthesized). That is, observe a signal of the signal generator concurrently (or alternately) with the tested signal using the spectrum analyzer while setting the frequency of the signal generator to the position of the dip on the screen of the spectrum analyzer, and determine the frequency of the signal generator at the time as a measured value.

## 7.5 Test Result

Temperature:	25°C		
Humidity:	55 % RH	Test Voltage	DC 5V


Condition	Frequency (MHz)	Measured Frequency (MHz)	Frequency Error (Hz)	Deviation (ppm)	Limit (ppm)	Verdict
NVNT	2402	2402	0	0	50	Pass
NVNT	2441	2441	0	0	50	Pass
NVNT	2480	2480	0	0	50	Pass





## 8. Antenna Power

### 8.1 Block Diagram Of Test Setup



### 8.2 Limit

Item	Limits
Antenna Power Density	(1) $\leq 3\text{mW/MHz}$ (FH, FH+DS, FH+OFDM form 2400 - 2483.5 MHz) (2) $\leq 10\text{mW/MHz}$ (OFDM OBW < 26MHz, DS, FH other than (1) ) (3) $\leq 5\text{mW/MHz}$ (OFDM OBW 26-38MHz) (4) $\leq 10\text{mW}$ (Other than (1) & (2)& (3))
Antenna Power Error	+20%, -80% (Base on manufacturer declare antenna power density)

### 8.3 Measuring Instruments And Setting

Please refer to section 5 in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
RB / VB	1 MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

### 8.4 Test Procedure

1. A power meter is connected on the IF output port of the spectrum analyzer.
2. Adjust the spectrum analyzer to have the center frequency the same with the measured carrier. RBW=VBW=1MHz, detector mode is positive peak. Turn off the averaging function and use zero span.
3. The calibrating signal power shall be reduced to 0 dBm and it shall be verified that the power meter reading also reduces by 10 dB.
4. Connect the equipment to be measured. Using the following settings of the spectrum analyzer in combination with "max hold" function, find the frequency of highest power output in the power envelope: center frequency equal to operating frequency; RBW & VBW: 1 MHz; detector mode: positive peak; averaging: off; span: 3 times the spectrum width; amplitude: adjust for middle of the instrument' range. The frequency found shall be recorded.
5. Set the center frequency of the spectrum analyzer to the found frequency and switch to zero span. The power meter indicates the measured power density "E".
6. Calculate antenna power density by the formula below  $PD = P / \text{Spread bandwidth}$ .
7. Antenna Power Error is definition that actual measure antenna power tolerance between + 20% to - 80% power range that base on manufacturer declare the conducted power density.




## 8.5 Test Result

Temperature:	25°C		
Humidity:	55 % RH	Test Voltage	DC 5V


Condition	Mode	Power (dBm)	Antenna Power (mW)	90% OBW (MHz)	Conducted RF output power density (mW/MHz)	Rated power density (mW/MHz)	Limit (mW/MHz)	Tolerance (%)	Verdict
NVNT	1-DH1	1.3	1.35	71.526	0.019	0.050	3	-62	Pass
NVNT	2-DH1	2.66	1.85	71.742	0.026	0.050	3	-48	Pass
NVNT	3-DH1	2.8	1.91	71.614	0.027	0.050	3	-46	Pass

Limit: +20%, -80% (Base on manufacturer declare antenna power density)  
 Conducted RF output power density=Antenna Power/ 90%Hopping Occupied bandwidth



## 9. Occupied Bandwidth

### 9.1 Block Diagram Of Test Setup



### 9.2 Limit

Item	Limits
Occupied Band Width:	FH 83.5MHz; OFDM,DS $\leq$ 26MHz;Others $\leq$ 26MHz
Spreading Bandwidth:	$\geq$ 500 kHz (FH, DS)
Spreading Factor	$\geq$ 5

### 9.3 Test Procedure

- Setting of SA is following as: RB: 1MHz / VB:1MHz / SPAN: 120MHz / AT: 20dB Ref: 10dBm / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak / Trace mode: Max hold
- EUT have transmitted the maximum modulation signal and fixed channelize (For DSSS or OFDM Device) or continuous maximum power of hopping mode (For FHSS Device). SA set to 99% of occupied bandwidth to measure occupied bandwidth. The limit is less than 26MHz (For DSSS or OFDM Device) or 83.5MHz (For FHSS Device).
- SA set to 90% of occupied bandwidth to measure Spread Spectrum Bandwidth and must greater than 500kHz.
- Spread Spectrum Factor = Spread Spectrum Bandwidth / modulation rate of EUT.
- Spread Spectrum Factor limit is greater than 5


### 9.4 Test Result

Temperature:	25°C		
Humidity:	55 % RH	Test Voltage	DC 5V



Test Condition	Mode	99% OBW (MHz)	90% OBW (MHz)	Spreading Factor	Verdict
NVNT	GFSK	78.728	71.526	71.526	Pass
NVNT	$\pi/4$ -DQPSK	78.819	71.742	35.871	Pass
NVNT	8DPSK	78.721	71.614	23.871	Pass



Remark:

- Spreading Factor = (90%Hopping Mode(Occupied bandwidth)) / (transmission rate);
- Transmission Rate=(GFSK=1Mbps,  $\pi/4$ -DQPSK=2Mbps, 8DPSK=3Mbps)




SHENZHEN





## 10. Unwanted Emission Intensity Measurement

### 10.1 Block Diagram Of Test Setup



### 10.2 Limit

Item	RB / VB	Limits
TX Spurious Emission	100KHz	$\leq 0.25 \mu\text{W}$ (-36dBm) ( $30\text{MHz} \leq f \leq 1000\text{MHz}$ )
	1 MHz	$\leq 2.5 \mu\text{W}$ (-26dBm ( $1000\text{MHz} < f \leq 2387\text{MHz}$ ))
	1 MHz	$\leq 25 \mu\text{W}$ (-16dBm ( $2387\text{MHz} < f \leq 2400\text{MHz}$ ))
	1 MHz	$\leq 25 \mu\text{W}$ (-16dBm ( $2483.5\text{MHz} \leq f < 2496.5\text{MHz}$ ))
	1 MHz	$\leq 2.5 \mu\text{W}$ (-26dBm ( $2496.5\text{MHz} \leq f < 12500\text{MHz}$ ))

### 10.3 Measuring Instruments And Setting

Please refer to section 5 in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
RB / VB	1 MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

### 10.4 Test Procedure

- EUT have transmitted the maximum modulation signal and fixed channelize.
- Setting of SA is following as: Below 1GHz RB:100KHz / VB:100KHz  
Above 1GHz RB:1MHz / VB:1MHz / AT: 20dB Ref: 10dBm / Sweep time: Auto  
Sweep Mode: Continuous sweep / Detect mode: Positive peak  
Trace mode: Max hold
- Setting of SA is following as 30MHz and stop frequency 1000MHz Then to mark peak reading value + cable loss shall be less than  $0.25\mu\text{W}$ .
- Setting of SA is following as 1000MHz and stop frequency 2387MHz Then to mark peak reading value + cable loss shall be less than  $2.5\mu\text{W}$ .
- SA adjusted to start frequency 2387MHz and stop frequency 2400MHz: Then to mark peak reading value + cable loss shall be less than  $25\mu\text{W}$ .
- SA adjusted to start frequency 2483.5MHz and stop frequency 2496.5MHz Then to mark peak reading value + cable loss shall be less than  $25\mu\text{W}$
- SA adjusted to start frequency 2496.5MHz and stop frequency 12500MHz Then to mark peak reading value + cable loss shall be less than  $2.5\mu\text{W}$

## 10.5 Test Result


Temperature:	25°C		
Humidity:	55 % RH	Test Voltage	DC 5V
Test Mode:	No-hopping		

Condition	Mode	Frequency (MHz)	Range (MHz)	Emission Frequency (MHz)	Max Value (dBm)	Limit Start (dBm)	Limit Stop (dBm)	Verdict
NVNT	1-DH1	2402	30-1000	833.16	-67.35	-36	-36	Pass
NVNT	1-DH1	2402	1000-2387	1497.93	-55.57	-26	-26	Pass
NVNT	1-DH1	2402	2387-2400	2400	-40.65	-16	-16	Pass
NVNT	1-DH1	2402	2483.5-2496.5	2488.4	-56.66	-16	-16	Pass
NVNT	1-DH1	2402	2496.5-13000	12716.41	-52.18	-26	-26	Pass
NVNT	1-DH1	2441	30-1000	742.95	-66.81	-36	-36	Pass
NVNT	1-DH1	2441	1000-2387	1459.1	-56.04	-26	-26	Pass
NVNT	1-DH1	2441	2387-2400	2399.84	-56.08	-16	-16	Pass
NVNT	1-DH1	2441	2483.5-2496.5	2492.68	-56.75	-16	-16	Pass
NVNT	1-DH1	2441	2496.5-13000	5248.42	-44.5	-26	-26	Pass
NVNT	1-DH1	2480	30-1000	763.32	-67.06	-36	-36	Pass
NVNT	1-DH1	2480	1000-2387	2277.43	-56.24	-26	-26	Pass
NVNT	1-DH1	2480	2387-2400	2399.69	-57.34	-16	-16	Pass
NVNT	1-DH1	2480	2483.5-2496.5	2483.76	-53.05	-16	-16	Pass
NVNT	1-DH1	2480	2496.5-13000	12600.87	-51.89	-26	-26	Pass
NVNT	2-DH1	2402	30-1000	835.1	-67.3	-36	-36	Pass
NVNT	2-DH1	2402	1000-2387	2314.88	-55.22	-26	-26	Pass
NVNT	2-DH1	2402	2387-2400	2399.96	-31.29	-16	-16	Pass
NVNT	2-DH1	2402	2483.5-2496.5	2485.42	-57.22	-16	-16	Pass
NVNT	2-DH1	2402	2496.5-13000	4807.27	-51.99	-26	-26	Pass
NVNT	2-DH1	2441	30-1000	742.95	-66.88	-36	-36	Pass
NVNT	2-DH1	2441	1000-2387	1783.66	-51.13	-26	-26	Pass
NVNT	2-DH1	2441	2387-2400	2387.59	-56.91	-16	-16	Pass
NVNT	2-DH1	2441	2483.5-2496.5	2490.91	-55.04	-16	-16	Pass
NVNT	2-DH1	2441	2496.5-13000	3504.84	-48.12	-26	-26	Pass
NVNT	2-DH1	2480	30-1000	31.94	-54.36	-36	-36	Pass
NVNT	2-DH1	2480	1000-2387	2339.84	-56.21	-26	-26	Pass
NVNT	2-DH1	2480	2387-2400	2399.94	-56.49	-16	-16	Pass
NVNT	2-DH1	2480	2483.5-2496.5	2483.5	-53.07	-16	-16	Pass
NVNT	2-DH1	2480	2496.5-13000	12768.92	-52	-26	-26	Pass
NVNT	3-DH1	2402	30-1000	31.94	-54.66	-36	-36	Pass
NVNT	3-DH1	2402	1000-2387	1497.93	-55.45	-26	-26	Pass
NVNT	3-DH1	2402	2387-2400	2399.96	-30.36	-16	-16	Pass
NVNT	3-DH1	2402	2483.5-2496.5	2494.76	-56.26	-16	-16	Pass
NVNT	3-DH1	2402	2496.5-13000	5258.92	-42.53	-26	-26	Pass
NVNT	3-DH1	2441	30-1000	31.94	-52.51	-36	-36	Pass
NVNT	3-DH1	2441	1000-2387	1457.71	-56.58	-26	-26	Pass




NVNT	3-DH1	2441	2387-2400	2398.08	-56.34	-16	-16	Pass
NVNT	3-DH1	2441	2483.5-2496.5	2484.93	-56.93	-16	-16	Pass
NVNT	3-DH1	2441	2496.5-13000	3567.86	-51	-26	-26	Pass
NVNT	3-DH1	2480	30-1000	31.94	-52.09	-36	-36	Pass
NVNT	3-DH1	2480	1000-2387	2199.76	-56.68	-26	-26	Pass
NVNT	3-DH1	2480	2387-2400	2392.34	-57.72	-16	-16	Pass
NVNT	3-DH1	2480	2483.5-2496.5	2484.01	-53.31	-16	-16	Pass
NVNT	3-DH1	2480	2496.5-13000	5258.92	-41.24	-26	-26	Pass



CO., LTD















SHENZHEN

















CO. LTD








CHENZHEN



























CHENZHEN























CO. LTD




CHENZHEN












Temperature:	25°C		
Humidity:	55 % RH	Test Voltage	DC 5V
Test Mode:	Hopping		

Condi-tion	Mode	Range (MHz)	Emission Frequency (MHz)	Max Value (dBm)	Limit Start (dBm)	Limit Stop (dBm)	Verdict
NVNT	1-DH1	30-1000	31.94	-57.41	-36	-36	Pass
NVNT	1-DH1	1000-2387	2170.63	-56.1	-26	-26	Pass
NVNT	1-DH1	2387-2400	2399.39	-55.5	-16	-16	Pass
NVNT	1-DH1	2483.5-2496.5	2485.06	-54.61	-16	-16	Pass
NVNT	1-DH1	2496.5-13000	5248.42	-41.22	-26	-26	Pass





CO.LTD






CHENZHEN



## 11. Radio Interference Prevention Capability Measurement

### 11.1 Block Diagram Of Test Setup



### 11.2 Limit

Item	Limits
Identification code	$\geq 48$ bits

### 11.3 Measuring Instruments And Setting

Item	Limits
MAC IP List	MAC Scan

### 11.4 Test Procedure

1. In the case that the EUT has the function of automatically transmitting the identification code:
  - a. Transmit the predetermined identification codes form EUT.
  - b. Check the transmitted identification codes with the demodulator.
2. In the case of receiving the identification ocde:
  - a. Transmit the predetermined identification codes form the counterpart.
  - b. Check if communication is normal.
  - c. Transmit the signals other than predetermined ID codes form the counterpart.
  - d. check if the EUT stops the transmission, or if it displays that idnetification codes are different from the predetermined ones.


### 11.5 Test Result

Temperature:	25°C		
Humidity:	55 % RH	Test Voltage	DC 5V

1. Bluetooth Device Address: 56-2b-6c-b8-8f-43
2. Test result PASS

## 12. Dwell Time

### 12.1 Block Diagram Of Test Setup



### 12.2 Limit

Item	Limits
Hopping Freq. Dwell Time	$\leq 0.4 \text{ sec (In } 0.4 \text{ sec} \times \text{ spreading rate)}$

### 12.3 Measuring Instruments And Setting

Please refer to section 5 in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	0 Hz
RB	1 MHz
VB	1 MHz
Detector	Peak
Trace	Max Hold
Sweep	Continuous

### 12.4 Test Procedure

1. The transmitter output (antenna port) was connected to the spectrum analyzer
2. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
3. Use a video trigger with the trigger level set to enable triggering only on full pulses.
4. Sweep Time is more than once pulse time.
5. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
6. Measure the maximum time duration of one single pulse.
7. Set the EUT for DH5, DH3 and DH1 packet transmitting.
8. Measure the maximum time duration of one single pulse.
9. Dwell time =  $[\text{spreading rate}/79] \times \text{duty-cycle} \times 0.4 \text{ seconds}$ . (to be determined for each mode, DH1, DH3, DH5)

## 12.5 Test Result


Temperature:	25°C		
Humidity:	55 % RH	Test Voltage	DC 5V



Condition	Mode	Fre- quency (MHz)	Spreading Bandwith (MHz)	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2441	71.526	0.367	105.329	287	28610.4	400	Pass
NVNT	1-DH3	2441	71.554	1.624	222.488	137	28621.6	400	Pass
NVNT	1-DH5	2441	71.576	2.872	318.792	111	28630.4	400	Pass
NVNT	2-DH1	2441	71.742	0.377	108.953	289	28696.8	400	Pass
NVNT	2-DH3	2441	71.621	1.629	231.318	142	28648.4	400	Pass
NVNT	2-DH5	2441	71.619	2.877	244.545	85	28647.6	400	Pass
NVNT	3-DH1	2441	71.614	0.377	108.576	288	28645.6	400	Pass
NVNT	3-DH3	2441	71.565	1.629	236.205	145	28626	400	Pass
NVNT	3-DH5	2441	71.547	2.879	276.384	96	28618.8	400	Pass

Note:



Period Time= Spreading Bandwidth \*0.4

Dwell Time= Pulse Time\* Burst Count









CO. LTD




SHENZHEN















TEST  
 TO  
 OVER  
 t See













CO. LTD






SHENZHEN


















CO. LTD



SHENZHEN


**13. Carrier Sense**

Not applicable, Since the EUT belong to Bluetooth



## 14. Imitation Of Collateral Emission Of Receiver Measurement

### 14.1 Block Diagram Of Test Setup



### 14.2 Limit

Item	Limits
RX Spurious Emission:	$\leq 4\text{nW}$ (-54dBm) ( $f < 1\text{GHz}$ )
	$\leq 20\text{nW}$ (-47dBm) ( $1\text{GHz} \leq f$ )

### 14.3 Measuring Instruments And Setting

Please refer to section 5 in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
RB	100 kHz (below 1GHz emissions) 1 MHz (above 1GHz emissions)
VB	100 kHz (below 1GHz emissions) 1 MHz (above 1GHz emissions)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

### 14.4 Test Procedure

- EUT have the continuous reception mode and fixed only one channelize.
- Setting of SA is following as RB / VB: 100 kHz (below 1GHz emissions) / 1 MHz (above 1GHz emissions)  
AT: 6dB / Ref: -20dBm / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak / Trace mode: Max hold
- SA set RB: 100kHz and VB: 100kHz. Then adjust to start frequency 30MHz and stop frequency 1000MHz. Search to mark peak reading value + cable loss shall be less than 4nW
- SA set RB: 1MHz and VB: 1MHz. Then adjust to start frequency 1000MHz and stop frequency 12500MHz. Search to mark peak reading value + cable loss shall be less than 20nW
- If power level of lower emissions are more than 1/10 of limit (.4nW for  $f < 1\text{GHz}$ , 2nW for  $f \geq 1\text{GHz}$ ), all those are to be indicated in the 2nd and 3rd lines. If others are 1/10 or less more of the limit, no necessary to be indicated.


## 14.5 Test Result


Temperature:	25°C		
Humidity:	55 % RH	Test Voltage	DC 5V



Condition	Mode	Frequency (MHz)	Range (MHz)	Emission Frequency (MHz)	Max Value (dBm)	Limit (dBm)	Verdict
NVNT	1-DH1	2402	30-1000	31.94	-71.47	-54	Pass
NVNT	1-DH1	2402	1000-13000	5176	-51.26	-47	Pass
NVNT	1-DH1	2441	30-1000	31.94	-71.81	-54	Pass
NVNT	1-DH1	2441	1000-13000	12640	-62.61	-47	Pass
NVNT	1-DH1	2480	30-1000	31.94	-72.19	-54	Pass
NVNT	1-DH1	2480	1000-13000	12568	-62.42	-47	Pass

All the modes were tested and only recorded the worst mode in the report.

TEC  
TC  
OVB  
t See










CO. LTD






### 15. EUT Photographs

EUT Photo 1





EUT Photo 2



NOTE: Appendix-Photographs Of EUT Constructional Details.

### 16. EUT Test Setup Photographs

#### Measurement Photos



TEST  
TC  
OVED  
t Seal

**STATEMENT**

1. The equipment lists are traceable to the national reference standards.
2. The test report can not be partially copied unless prior written approval is issued from our lab.
3. The test report is invalid without the "special seal for inspection and testing".
4. The test report is invalid without the signature of the approver.
5. The test process and test result is only related to the Unit Under Test.
6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.
7. The quality system of our laboratory is in accordance with ISO/IEC17025.
8. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

**Address:**

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: <http://www.chnbctc.com>

Consultation E-mail: [bctc@bctc-lab.com.cn](mailto:bctc@bctc-lab.com.cn)

Complaint/Advice E-mail: [advice@bctc-lab.com.cn](mailto:advice@bctc-lab.com.cn)

※※※※※ END ※※※※※

